

旋转式抓木器/抓石器

HYDRAULIC GRAPPLE



主要特点 MAIN FEATURE

- 采用特殊钢材，质地轻，弹性高，耐磨性高。
- 具有刹车制动功能，采用新型涡轮蜗杆式设计。
- 同级较大开档宽度，较小重量及较大性能
- 可顺时针，逆时针360度自由旋转
- 使用特制的旋转齿轮，延长了产品寿命，降低维护费用
- Made of special steel, it is lightweight, highly elastic and has high wear resistance.
- It has braking function and adopts new turbine and worm design.
- Largest opening width, smaller weight and greater performance in its class.
- Can rotate freely 360 degrees clockwise and counterclockwise.
- The use of special rotating gears extends product life and reduces maintenance costs



适用范围

scope of application

* 可进行石材作业，木材甘蔗作业，废弃物作业，管材作业，园林操作，砌石工程等所有夹装作业

* Versatile applications including handling of stones, wood, cane, pipes, disposable waste, landscaping works and many others.

抓木器 / 抓石器参数 PARAMETER

| 型号 Model | 单位 Unit | BYKL 02 | BYKL 04 | BYKL 06 | BYKL 08 | BYKL 10 | BYKL 14 | BYKL 20 |
|---------------------------|--------------------|---------|---------|---------|---------|---------|---------|---------|
| 重量 Weight | Kg | 360 | 440 | 900 | 1850 | 2130 | 2600 | 2800 |
| 最大开口 Max jaw opening | mm | 1200 | 1400 | 1600 | 2100 | 2500 | 2800 | 2800 |
| 工作压力 Oil Pressure | kg/cm ² | 110-140 | 120-160 | 150-170 | 160-180 | 160-180 | 180-200 | 180-200 |
| 设定压力 Operating flux | kg/cm ² | 170 | 180 | 190 | 200 | 210 | 250 | 250 |
| 工作流量 Cylinder Volume | L/min | 30-55 | 50-100 | 90-110 | 100-140 | 130-170 | 200-250 | 200-320 |
| 油缸容量 Suitable excavator | Ton | 4×2 | 4.5×2 | 8.0×2 | 9.7×2 | 12×2 | 12×2 | 14×2 |
| 适用挖机 Applicable Excavator | Ton | 4-6 | 7-11 | 12-16 | 17-23 | 24-30 | 31-40 | 41-50 |

我们的产品一直在升级中，由于技术原因的变更不做另行通知。

Our products are always being improved and are subject to change without notice due to technical reasons.